

zanche e sostegni / brackets and mounts

zanche a camino / chimney brackets

codice code	descrizione description	lunghezza length cm	palo mast ø mm	zincatura finish	imballo packing Pcs	utilizzo use
411	Zanca a camino, spessore 3 mm (411) e 4 mm (411R).	-	20÷40	ZF	6	Per il fissaggio di pali per antenne TV a camino (tirante non fornito).
411R	<i>Chimney bracket, thickness 3 mm (411) and 4 mm (411R).</i>	-	20÷40	ZF	6	<i>For the fixing of chimney masts for TV aerials (tension rod not supplied).</i>
411F	Zanca Unica. Zanca a camino con piastra 90° (lato 25 cm), spessore 2,5 mm. <i>Single bracket. Chimney bracket with 90° plate (side 25 cm), thickness 2,5 mm.</i>	16	30÷50	ZB	1	Per il fissaggio a camino di pali per parabole di piccolo e medio Ø o per antenne TV. Utilizzare il nastro in acciaio zincato (optional) cod. NFK e NFK5. <i>For the chimney fixing of masts for dishes of small and medium diameter or for TV aerials. The galvanised steel strip (optional) code NFK and NFK5 can be used.</i>
411F2	2 zanche separate. Coppia zanche a camino (spessore lamiera 2,5 mm). <i>2 separated brackets. Pair of Chimney brackets (sheet thickness 2,5 mm).</i>	22	30÷50	ZB	1	
411K	Zanca (1 pezzo). <i>Single bracket.</i>	22	30÷50	ZF	1	
NFK	Nastro in acciaio zincato 40x0,5 mm.	-	-	-	conf. 25mt	
NFK5	<i>Galvanized steel strip 40x0,5 mm.</i>	-	-	-	conf. 5mt	

