

Amplifiers

WIDEBAND INDOOR AMPLIFIER

NEW



7720 | 7720L



- 1 wideband input: 47-862 MHz (VHF-UHF)
- 2 outputs
- adjustable gain: 13-28 dB
- power LED indicator
- wall and DIN rail mountable

		7720	7720L
Frequency range	MHz	47-862	47-790
Adjustable gain	dB	13-28	
Noise figure	dB	4,0	
Max. output level	dBμV	101	
Return loss (input/output)	dB	10	
Isolation between outputs	dB	15	
Power	-	230V~/4VA	
Dimensions	mm	110 x 94 x 41	

VHF/UHF INDOOR AMPLIFIER

NEW



7722 | 7722L



- 1 input: 40-320 MHz + 470-862 MHz (790 MHz for L version)
- 2 outputs
- adjustable VHF gain: 15-30 dB
- adjustable UHF gain: 18-28 dB
- power LED indicator
- 24 Vdc switchable remote power (7722L only)
- wall and DIN rail mountable (7722L only)

		7722	7722L
Frequency range	MHz	40-320 + 470-862	40-320 + 470-790
Adjustable gain	dB	VHF: 15-30/UHF: 18-28	
Noise figure	dB	3,0	
Max. output level*	dBμV	107	
Return loss (input/output)	dB	10	
Isolation between outputs	dB	15	
Switchable remote power	-	no	yes (24V/55mA)
Power	-	230V~/6,9VA	
Dimensions	mm	102 x 76 x 54	137 x 92 x 42

*Terr.: -60 dBc/IM3