

compact  
easy

## Charging simplified

Start your day with a full charge in the morning. After setting the maximum dedicated power during installation, simply let the WB manage the charging process. Connect your vehicle to the house, and charging will commence automatically. The **Easy Wallbox** is compact and efficient, providing essential information through intuitive LED signals. It strikes an excellent balance between simplicity and functionality.

Available in **7.4kW** and **22kW** versions.



<b>Standard</b>	IEC 61851-1:2019
<b>Electrical features</b>	
AC / DC	AC
Mode	Mode 3
Input voltage	230Vac single phase 400Vac three-phase
Frequency	50 / 60 Hz
Max. voltage	32 A
Max. power	7,4 kW single phase 22 kW three-phase
Power modulation	Toroid included
MID Meter	-
Energy measurement	Integrated (+-5%)
<b>General specifications</b>	
Housing Design	Compact
Casing material	Polycarbonate
Visual interface	Display LED
Splash resistance	IP54
Mechanical resistance	IK07
Operating temperature	-20° / +45°
Operating Humidity	5% / 95%
Installation	wall Floor with Kit Open Space
Dimensions (cables excluded) mm	155 x 210 x 92
Weight	4Kg
<b>Connections</b>	
Cable/Socket	cable 5 mt
Connector	1 x Type 2
<b>Connectivity</b>	
Ethernet	-
Wi-Fi	only for configuration
4G LTE	-
RFID	-
RS485	yes*
<b>Interconnection and configuration</b>	
OCCP	-
Master/Slave function	Slave only
Web App	-
Configuration	local Wi-Fi
Photovoltaic mode	-

Cod.	Description
<b>GW7C</b>	Wallbox 7.4 KW, 5 m single-phase type 2 EASY cable
<b>GW11CT</b>	Wallbox 11 KW, 5 m three-phase type 2 EASY cable
<b>GW22CT</b>	Wallbox 22 KW, 5 m three-phase type 2 EASY cable

(\*): RS485 connectivity for the Slave function only